



# 2018 Drag Tire Guide



[www.racegoodyear.com](http://www.racegoodyear.com)

# Drag Tire Compound Data

<b>Compound</b>	<b>Primary Application Vehicle</b>
D-8	High grip compound for high horsepower radial tire applications
D-2A	High grip compound used for TAD and some bracket applications
D-2G	For Pro Mod and TAFC. High level of grip that can also sustain wheelspeed
D-2H	For TF/FC and other high horsepower applications
D-1	For use on dragsters and other lightweight cars
D-4B	For Stock Eliminator and slightly more tractive than D-4A
D-4A	Good for hot or slick track conditions
D-4	Excellent wear/longevity for heavy applications, +3,000 lbs.
D-1A	For use on Stock and Super Stock Radials
D-6	Works well on Dragsters and 1,500 - 2,500 lbs. cars
D-5	Works well on Dragsters and 2,000 - 3,200 lbs. cars
D-7	Limited application compound. Designed to eliminate shake
D-3	For heavy manual and automatic cars
HARD	Frontrunners

Listed in order from softest to hardest

Note that in some cases, a softer compound is not necessarily more tractive due to the nature of Goodyear's drag race compounds.



## Top Fuel & Funny Car

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	MSRP	Comments
231233	2747	D-2H	36.0x17.5-16	16	36.6	21.8	17.3	48.0	115.0	\$ 917.00	BL, LW

## Pro Mod, Alcohol, Pro Stock

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	MSRP	Comments
229258	3122	D-2G	34.5x17.0-16	16	34.8	21.3	17.0	43.0	109.00	\$ 546.00	
230875	3036	D-2G+	36.0x17.0-16	16	35.3	21.8	17.0	42.5	111.00	\$ 499.00	BL, LW
164841	1230	D-2A	36.0x17.0-16	16	36.3	21.4	17.0	49.1	114.00	\$ 620.00	BL
233411	2433	D-4A	33.5x17.0-16	16	33.4	21.5	17.7	43.0	105.00	\$ 665.00	BL, SS
230874	2912		Shield							\$ 171.00	

**Western Region**  
 Carrol Shelby Enterprises, Inc.  
 Las Vegas, Nevada  
 Phone - 702.430.5160  
[www.carrolshelbyent.com](http://www.carrolshelbyent.com)

**Central Region**  
 Carter-Maxwell, Inc.  
 Bethany, Oklahoma  
 Phone - 405.789.8253

**Eastern Region**  
 Shelby Carter Maxwell, Inc.  
 High Point, North Carolina  
 Phone - 336.884.0328

**Canada**  
 Fairchild Race Tire  
 Fenwick, Ontario  
 Phone - +1.905.641.8633  
[www.fcracetires.com](http://www.fcracetires.com)

\*\*\* Rim width tolerance is plus or minus one inch from specified Rim Width \*\*\*  
 Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall  
**ET** - Extended tread life, **MC** - Motorcycle front, **BL** - Bead lock wheel required



# Stock, Super Stock

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	MSRP	Comments
210598	2790	D-5	28.0x9.0-15	8	28.0	10.7	9.0	21.3	88.0	\$ 219.00	
210599	2791	D-5	28.0x10.0-15	10	28.0	12.0	10.0	23.1	88.0	\$ 224.00	
210596	2796	D-5	29.0x11.0-15	10	29.0	12.8	10.9	25.1	91.0	\$ 260.00	
210597	2797	D-5	29.0x12.0-15	11	29.0	13.9	11.8	25.1	91.0	\$ 267.00	
219253	4465	D-8	30.0x10.5-15	10	29.6	13.3	10.5	23.5	93.0	\$ 292.00	R
23623	1909	D-5	30.0x9.0-15	8	30.7	12.4	9.0	25.0	96.5	\$ 288.00	
190161	2018	D-5	31.0x13.0-15	12	30.6	15.6	12.8	33.4	96.0	\$ 372.00	MS
219043	4459	D-8	31.0x13.5-15	14	31.7	16.9	13.8	33.0	99.5	\$ 345.00	
190162	2019	D-5	31.0x14.0-15	12	31.0	16.2	14.0	35.8	97.0	\$ 376.00	MS
219042	4461	D-8	32.0x14.0-15	14	32.1	17.2	13.8	32.4	101.0	\$ 374.00	R
23556	1984	D-5	32.0x14.0-15	14	32.4	17.0	14.4	39.3	101.0	\$ 398.00	
23540	1672	D-5	32.0x14.5-15	14	32.8	17.7	14.8	39.4	103.0	\$ 399.00	
190163	2070	D-6	33.0x14.5-15	14	32.8	18.9	14.9	34.1	104.0	\$ 397.00	
233899	4827	D-1A	30.0x9.0-15	9	29.5	11.8	9.0	22.7	92.5	\$ 291.00	R, LW
236033	4892	D-1A	30.0x9.0-15	9	29.5	11.8	9.1	21.1	92.5	\$ 291.00	R, LW
236035	4894	D-1A	30.0x9.0-15	9	30.0	12.0	9.1	21.4	94.0	\$ 291.00	R, LW

### Western Region

Carrol Shelby Enterprises, Inc.  
Las Vegas, Nevada  
Phone - 702.430.5160  
[www.carrolshelbyent.com](http://www.carrolshelbyent.com)

### Central Region

Carter-Maxwell, Inc.  
Bethany, Oklahoma  
Phone - 405.789.8253

### Eastern Region

Shelby Carter Maxwell, Inc.  
High Point, North Carolina  
Phone - 336.884.0328

### Canada

Fairchild Race Tire  
Fenwick, Ontario  
Phone - +1.905.641.8633  
[www.fcracetires.com](http://www.fcracetires.com)

\*\*\* Rim width tolerance is plus or minus one inch from specified Rim Width \*\*\*

Comments: R - Radial, HG - High Growth, LW - Lightweight, MS - Medium stiff sidewall, SS - Stiff sidewall

ET - Extended tread life, MC - Motorcycle front, BL - Bead lock wheel required



# Super Gas

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	MSRP	Comments
23556	1984	D-5	32.0x14.0-15	14	32.4	17.0	14.4	39.3	101	\$ 398.00	MS
23540	1672	D-5	32.0x14.5-15	14	32.8	17.7	14.8	39.4	103	\$ 399.00	MS
23558	1408	D-5	32.0x16.0-15	15	32.4	18.4	16.0	39.6	102	\$ 404.00	MS
190102	2051	D-4A	32.5x17.0-15	15	32.5	20.8	17.2	41.1	100	\$ 462.00	
192212	2078	D-5	33.0x15.0-15	14	33.2	17.5	15.0	40.6	104	\$ 405.00	MS
190167	2052	D-6	33.0x16.0-15	15	32.8	19.6	16.1	38.0	102	\$ 414.00	
191202	2053	D-4A	33.0x17.0-15	15	32.8	20.6	17.3	42.9	102	\$ 462.00	SS
233411	2433	D-4A	33.5x17.0-16	16	33.4	21.5	17.7	43.0	105	\$ 665.00	BL, SS
228522	2211	D-4A	33.5x17.0-16	16	33.4	21.2	17.5	42.5	105	\$ 460.00	BL, SS
227639	2775	D-2A	33.5x17.0-16	16	33.5	21.1	16.8	40.3	105	\$ 463.00	BL
235137	2776	D-2A	33.5x17.0-16	16	33.5	21.1	16.8	45.1	105	\$ 464.00	BL, SS

**Western Region**  
 Carrol Shelby Enterprises, Inc.  
 Las Vegas, Nevada  
 Phone - 702.430.5160  
[www.carrolshelbyent.com](http://www.carrolshelbyent.com)

**Central Region**  
 Carter-Maxwell, Inc.  
 Bethany, Oklahoma  
 Phone - 405.789.8253

**Eastern Region**  
 Shelby Carter Maxwell, Inc.  
 High Point, North Carolina  
 Phone - 336.884.0328

**Canada**  
 Fairchild Race Tire  
 Fenwick, Ontario  
 Phone - +1.905.641.8633  
[www.fcracetires.com](http://www.fcracetires.com)

\*\*\* Rim width tolerance is plus or minus one inch from specified Rim Width \*\*\*

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall

**ET** - Extended tread life, **MC** - Motorcycle front, **BL** - Bead lock wheel required



## Motorcycle

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	MSRP	Comments
103310	2980	D-6	25.0x7.0-18	6	25.4	7.0	6.6	11.3	80.0	\$ 219.00	BL, LW

## Frontrunner

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	MSRP	Comments
177193	1445	HARD	22.0x2.5-17	2.5	22.0	2.5	1.5	4.5	69.9	\$ 195.00	ET
215560	2904	HARD	22.0x4.0-17	2.5	22.9	3.4	3.1	5.2	72	\$ 272.00	
189891	1961	HARD	23.0x5.0-15	4	23.0	6.8	5.0	12.2	72.7	\$ 240.00	
189955	1962	HARD	24.0x5.0-15	4	24.0	6.8	5.0	11.3	75.8	\$ 204.00	
215499	2991	HARD	25.0x4.5-15	4	25.0	6.5	4.5	11.6	78.5	\$ 207.00	LW
190130	1964	HARD	26.0x4.5-15	4	26.0	6.3	4.5	10.8	81.2	\$ 210.00	
197495	1965	HARD	27.0x4.5-15	4	27.0	7.9	4.5	13.5	84.8	\$ 211.00	
189822	1966	HARD	28.0x4.5-15	4	28.0	7.7	5.1	12.4	89.1	\$ 213.00	

**Western Region**  
 Carrol Shelby Enterprises, Inc.  
 Las Vegas, Nevada  
 Phone - 702.430.5160  
[www.carrolshelbyent.com](http://www.carrolshelbyent.com)

**Central Region**  
 Carter-Maxwell, Inc.  
 Bethany, Oklahoma  
 Phone - 405.789.8253

**Eastern Region**  
 Shelby Carter Maxwell, Inc.  
 High Point, North Carolina  
 Phone - 336.884.0328

**Canada**  
 Fairchild Race Tire  
 Fenwick, Ontario  
 Phone - +1.905.641.8633  
[www.fcracetires.com](http://www.fcracetires.com)

\*\*\* Rim width tolerance is plus or minus one inch from specified Rim Width \*\*\*  
 Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall  
**ET** - Extended tread life, **MC** - Motorcycle front, **BL** - Bead lock wheel required



## Comp eliminator, Super Comp

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	MSRP	Comments
206637	2585	D-3	31.0x12.0-15	12	30.8	15.2	12.0	22.6	96.5	\$ 380.00	
193992	1911	D-1	32.0x14.5-15	14	32.2	17.7	15.0	34.1	101	\$ 399.00	
190102	2051	D-4A	32.5x17.0-15	15	32.5	20.8	17.2	41.1	100	\$ 462.00	LW, SS
23654	1288	D-7	33.0x12.0-15	12	32.4	16.5	12.3	28.8	102	\$ 392.00	HG
190163	2070	D-6	33.0x14.5-15	14	32.8	18.9	14.9	34.1	104	\$ 397.00	
215174	2533	D-2A	33.0x16.0-15	15	32.4	19.9	16.3	39.6	106	\$ 377.00	
190167	2052	D-6	33.0x16.0-15	15	32.8	19.6	16.1	38.0	102	\$ 414.00	
215232	2534	D-2A	33.0x17.0-15	15	32.4	20.5	17.4	39.5	104	\$ 389.00	
227639	2775	D-2A	33.5x17.0-16	16	33.5	21.1	16.8	40.3	105	\$ 463.00	BL
235137	2776	D-2A	33.5x17.0-16	16	33.5	21.1	16.8	45.1	105	\$ 464.00	BL, SS

\*\*\* Rim width tolerance is plus or minus one inch from specified Rim Width \*\*\*

Comments: **R** - Radial, **HG** - High Growth, **LW** - Lightweight, **MS** - Medium stiff sidewall, **SS** - Stiff sidewall

**ET** - Extended tread life, **MC** - Motorcycle front, **BL** - Bead lock wheel required

[www.racegoodyear.com](http://www.racegoodyear.com)



# Landspeed

Material Number	D Number	Compound	Size	Rim Width	Average Diameter	Section Width	Tread Width	Weight Lbs.	Average Circ.	MSRP	Comments
215560	2904	HARD	22.0x4.0-17	2.5	22.9	3.4	3.1	5.2	72	\$ 272.00	
234517	2952	HARD	21.0x5.0-15	4.5	21.3	5.4	4.1	10.0	68.5	\$ 632.00	
234515	2953	HARD	23.0x5.0-15	4.5	23.1	7.0	5.0	12.0	74.2	\$ 656.00	
234514	2954	HARD	25.0x4.5-15	4.5	24.8	6.7	4.0	12.0	79.0	\$ 662.00	
234516	2956	HARD	28.0x4.5-15	4.5	27.8	7.7	4.5	13.0	88.4	\$ 690.00	
225063	2934	HARD	28.0x10.0-15	9.5	28.3	13.6	10.0	22.0	89.0	\$ 267.00	
233188	2870	HARD	30.0x9.0-18	6.5	30.0	8.5	3.0	16.5	93.0	\$ 734.00	LW

D Number	Min. PSI	Max Load	Max Speed
2904	90 psi	1200 lbs.	300 mph
2952	50 psi	1200 lbs.	300 mph
2953	70 psi	1700 lbs.	300 mph
2954	70 psi	1700 lbs.	300 mph
2956	70 psi	1700 lbs.	300 mph
2934	70 psi	1700 lbs.	300 mph
2870	70 psi	2300 lbs.	320 mph

**Western Region**  
**Carrol Shelby Enterprises, Inc.**  
*Las Vegas, Nevada*  
 Phone - 702.430.5160  
[www.carrolshelbyent.com](http://www.carrolshelbyent.com)

**Central Region**  
**Carter-Maxwell, Inc.**  
*Bethany, Oklahoma*  
 Phone - 405.789.8253

**Eastern Region**  
**Shelby Carter Maxwell, Inc.**  
*High Point, North Carolina*  
 Phone - 336.884.0328

**Canada**  
**Fairchild Race Tire**  
 Fenwick, Ontario  
 Phone - +1.905.641.8633  
[www.fcracetires.com](http://www.fcracetires.com)

\*\*\* Rim width tolerance is plus or minus one inch from specified Rim Width \*\*\*

Comments: R - Radial, HG - High Growth, LW - Lightweight, MS - Medium stiff sidewall, SS - Stiff sidewall

ET - Extended tread life, MC - Motorcycle front, BL - Bead lock wheel required